



ABHA-FS330079

9.6W/m 3X120 IP68 SINGLE COLOR STRIPLIGHT



PRODUCT SPECIFICATIONS

| | |
|------------------------|---|
| Strip Material | Double Sided Flexible PCB |
| IP68 Seal-out Material | Clear Silicone Rubber |
| Installation Tape | 3M Strong Adhesive Stick-on Tape |
| Dimmability | Compatible with Phase Dimming, 0 – 10V Dimming & DALI Dimming |
| Binning | 3 Step MacAdam |
| Life Span | 50,000 hours |

| | |
|-----------------------|---------------------------------------|
| LED Chip | Samsung |
| Number of LEDs | 600 per Reel (120 per Meter) |
| Power Consumption | 48W (5m) 96W (10m) |
| Input Voltage | 24VDC |
| Single LED Wattage | 0.08W |
| Input Voltage | 24VDC |
| Length | 10m or 5m |
| Strip Thickness | 2.5mm |
| Operating Temperature | from -20° to 50° C |
| Color Rendering Index | >85 |
| Warranty | 3 years against manufacturing defects |
| Agency Approval | CE, RoHS |



| Power (W) | Available color Temperatures | LED Chip Lumen Efficacy | | | IP Rating | Available Beam Angles |
|-----------|---|-------------------------|---------|---------|-----------|-----------------------|
| | | 3000K | 4000K | 6000K | | |
| 48W | 2400K 2700K 3000K 4000K 6000K RED, GREEN, BLUE RBG+W(2700K-6000K) | 110lm/W | 120lm/W | 130lm/W | 68 | 120° |

Standard option.

Non-standard products may be subject to MOQ. Contact your regional sales representative for more information.