




ELNUR-SL550095


100W STREET LIGHT



PRODUCT SPECIFICATIONS

| | |
|------------------|-----------------------|
| Fixture Material | Die-Cast Aluminium |
| Fixture Finish | Powder-coated RAL7016 |
| Lens | Clear optical lens |
| Glass | Clear tempered glass |
| Driver | Built-in |
| Binning | 3 Step MacAdam |
| Life Span | 50,000 hours |

| | |
|-----------------------|---------------------------------------|
| LED Chip | CREE |
| Power Consumption | 100W |
| Input Voltage | 180-240VAC, 50/60Hz |
| Operating Temperature | from -20° to 65° C |
| Color Rendering Index | ≥85 |
| Warranty | 3 years against manufacturing defects |
| Agency Approval | CE, RoHS |



| Power (W) | Available color Temperatures | LED Chip Lumen Efficacy | | | IP Rating | Available Beam Angles |
|-----------|----------------------------------|-------------------------|---------|---------|-----------|--|
| | | 3000K | 4000K | 6000K | | |
| 100W | 2700K 3000K 4000K 6000K | 110lm/W | 120lm/W | 130lm/W | 66 | Type II-Medium 65° x 155° Type II-Medium 80° x 155° |

Standard option.

Non-standard products may be subject to MOQ. Contact your regional sales representative for more information.