




## ELNUR-SL550095


### 100W STREET LIGHT



### PRODUCT SPECIFICATIONS

|                  |                      |
|------------------|----------------------|
| Fixture Material | Die-Cast Aluminium   |
| Fixture Finish   | Powder-coated Gray   |
| Lens             | Clear optical lens   |
| Glass            | Clear tempered glass |
| Driver           | Built-in             |
| Binning          | 3 Step MacAdam       |
| Life Span        | 50,000 hours         |

|                       |                                       |
|-----------------------|---------------------------------------|
| LED Chip              | CREE                                  |
| Power Consumption     | 100W                                  |
| Input Voltage         | 180-240VAC, 50/60Hz                   |
| Operating Temperature | from -20° to 65° C                    |
| Color Rendering Index | ≥85                                   |
| Warranty              | 3 years against manufacturing defects |
| Agency Approval       | CE, RoHS                              |



| Power<br>(W) | Available color<br>Temperatures  | LED Chip Lumen Efficacy |         |         | IP Rating | Available<br>Beam Angles                               |
|--------------|----------------------------------|-------------------------|---------|---------|-----------|--------------------------------------------------------|
|              |                                  | 3000K                   | 4000K   | 6000K   |           |                                                        |
| 100W         | 2700K<br>3000K<br>4000K<br>6000K | 110lm/W                 | 120lm/W | 130lm/W | 66        | Type II-Medium 65° x 155°<br>Type II-Medium 80° x 155° |

#### Standard option.

Non-standard products may be subject to MOQ. Contact your regional sales representative for more information.