


FOTIS-SP220009


20W LED SPIKE LIGHT



PRODUCT SPECIFICATIONS

Fixture Material	Die cast Aluminum
Fixture Finish	Powder-coated bronze
Glass	Clear Glass
Reflector	Polycarbonate with aluminum coating
Cowl Material	Die cast Aluminum
Binning	3 Step MacAdam
Wiring	1 meter of 2 core 0.75mm ² rubber cable
Life Span	50,000 hours

LED Chip	Nichia COB
Power Consumption	20W
Input Voltage	12VAC, 50/60 Hz or 12VDC
Operating Temperature	from -20° to 65° C
Color Rendering Index	≥85
Warranty	3 years against manufacturing defects
Agency Approval	CE, RoHS, ETL



Power (W)	Available color Temperatures	Luminous Flux			IP Rating	Available Beam Angles
		3000K	4000K	6000K		
20W	2700K 3000K 4000K 6000K	110lm/W	120lm/W	130lm/W	66	35° 60°

Standard option.

Non-standard products may be subject to MOQ. Contact your regional sales representative for more information.

ACCESSORIES

SPIKE



Spike for mounting fixture in the soil (default mounting accessory supplied with the fixture).

WALL MOUNT BRACKET



Wall mount bracket, can be used to mount fixture on posts, trees or walls (sold separately).

COWL



Small cowl for 4.5W and 8.5W spike light, used for focusing light (sold separately).