


FOTIS-SP220155


5W COMPACT LED SPIKE LIGHT



PRODUCT SPECIFICATIONS

Fixture Material	Die-cast Solid Brass
Fixture Finish	Brass
Glass	Clear Glass
Optic	High temperature Japanese Acrylic
Binning	3 Step MacAdam
Wiring	1 meter of 2 core 0.75mm ² rubber cable
Life Span	50,000 hours

LED Chip	Nichia COB
Power Consumption	5W
Input Voltage	12VAC, 50/60 Hz or 12VDC
Operating Temperature	from -20° to 65° C
Color Rendering Index	>85
Warranty	3 years against manufacturing defects
Agency Approval	CE, RoHS, ETL



Power (W)	Available color Temperatures	Luminous Flux			IP Rating	Available Beam Angles
		3000K	4000K	6000K		
5W	2700K 3000K 4000K 6000K	80lm/W	85lm/W	90lm/W	66	35°

Standard option.

Non-standard products may be subject to MOQ. Contact your regional sales representative for more information.

ACCESSORIES

SPIKE



Spike for mounting fixture in the soil (default mounting accessory supplied with the fixture).

WALL MOUNT BRACKET



Wall mount bracket, can be used to mount fixture on posts, trees or walls (sold separately).