


LUCIO-DW220248

4W RECESSED FOUR-SIDED DRIVEWAY LIGHT





PRODUCT SPECIFICATIONS

Fixture Material	Grade 316 Stainless Steel		
Fixture Finish	Polished Stainless Steel		
Sleeve Material	Black Polycarbonate		
Diffuser	Clear UV resistant polycarbonate		
Static Load Pressure	2500kg		
Driver	Built-in		
Binning	3 Step MacAdam		
Wiring	1 Meter of 3core 0.5mm² rubber cable		
Life Span	50,000 hours		

LED Chip	Nichia
Power Consumption	4W
Input Voltage	180-240VAC, 50/60 Hz. Also available in 12VAC, 50/60 Hz or 12VDC (IP67)
Operating Temperature	from -20° to 65° C
Color Rendering Index	>85
Driver Protection	Short circuit
Warranty	3 years against manufacturing defects
Agency Approval	CE, RoHS



Power Available color (W) Temperatures			In Daille	Available		
	3000K	4000K	6000K	IP Rating	Beam Angles	
4W	2700K 3000K 4000K 6000K	110lm/W	120lm/W	130lm/W	65	4x60°

Standard option.

Non-standard products may be subject to MOQ. Contact your regional sales representative for more information.