




**GLOBAL LIGHT
& POWER LLC**
AN LED LIGHTING COMPANY

MORCAN-UR220456

1W RECESSED UNDERWATER LIGHT



PRODUCT SPECIFICATIONS

Trim Material	Grade 316 Stainless Steel
Trim Finish	Polished Stainless steel
Glass	Tempered frosted glass
Fixture Material	Grade 316 Stainless Steel
Sleeve Material	Black Polycarbonate
Binning	3 Step MacAdam
Wiring	3 meter of 2 core 0.75mm ² rubber cable
Life Span	50,000 hours

LED Chip	Nichia
Power Consumption	1W
Input Voltage	12VAC, 50/60 Hz or 12VDC
Operating Temperature	from -20° to 65° C
Color Rendering Index	>85
Warranty	3 years against manufacturing defects
Agency Approval	CE, RoHS, ETL
Power Factor	>0.8



Power (W)	Available color Temperatures	Luminous Flux			IP Rating	Available Beam Angles
		3000K	4000K	6000K		
1W	2700K 3000K 4000K 6000K BLUE	110lm/W	120lm/W	130lm/W	65	120°

Standard option.

Non-standard products may be subject to MOQ. Contact your regional sales representative for more information.

ACCESSORIES

POLYVINYL CHLORIDE SLEEVE

Black polycarbonate sleeve to be used with recessed trail light.

