


## NANNA-WL220729

### 15W DOWNLIGHT WALL SCENCE



### PRODUCT SPECIFICATIONS

|                  |                                 |
|------------------|---------------------------------|
| Fixture Material | Die-cast Aluminium              |
| Fixture Finish   | Powder-coated Black             |
| Glass/Diffuser   | UV resistant opal polycarbonate |
| Driver           | Built-in                        |
| Binning          | 3 Step MacAdam                  |
| Life Span        | 50,000 hours                    |

|                       |                                       |
|-----------------------|---------------------------------------|
| LED Chip              | CREE                                  |
| Power Consumption     | 15W                                   |
| Input Voltage         | 180~240V AC, 50/60Hz                  |
| Operating Temperature | from -20° to 65° C                    |
| Color Rendering Index | >85                                   |
| Driver Protection     | Short circuit                         |
| Warranty              | 3 years against manufacturing defects |
| Agency Approval       | CE, RoHS                              |



| Power (W) | Available color Temperatures     | Luminous Flux |         |         | IP Rating | Available Beam Angles |
|-----------|----------------------------------|---------------|---------|---------|-----------|-----------------------|
|           |                                  | 3000K         | 4000K   | 6000K   |           |                       |
| 15W       | 2700K<br>3000K<br>4000K<br>6000K | 110lm/W       | 120lm/W | 130lm/W | 65        | 90°                   |