



NURU-FL440188

50W FLOOD LIGHT







PRODUCT SPECIFICATIONS

| Fixture Material | Die-cast aluminum |
|------------------|--|
| Fixture Finish | Powder-coated black |
| Glass | High-Intensity Tempered glass |
| Reflector | Polycarbonate with aluminum coating |
| Binning | 3 Step MacAdam |
| Wiring | 1 meter of 3 core 0.75mm rubber cable |
| Life Span | 108,000 hours |

| LED Chip | Philips |
|-----------------------|---------------------------------------|
| Power Consumption | 50W |
| Input Voltage | 180~240V AC, 50/60Hz |
| Operating Temperature | from -40° to 50° C |
| Color Rendering Index | >85 |
| Driver Protection | Short circuit |
| Warranty | 3 years against manufacturing defects |
| Agency Approvals | CE, RoHS |



| | Available color | LED Chip Lumen Efficacy | | IP Rating | Available |
|-----|-----------------|-------------------------|---------|-----------|--|
| | Temperatures | res 2200K | 6500K | ir kullig | Beam Angles |
| 50W | 2200K-6500K | 165lm/W | 170lm/W | 66 | 7° 15° 30° 60° 90° 120° |

Standard option.

Non-standard products may be subject to MOQ. Contact your regional sales representative for more information.