




**GLOBAL LIGHT
& POWER LLC**
AN LED LIGHTING COMPANY

SHAMA-PL111324

6W PENDANT LIGHT



PRODUCT SPECIFICATIONS

Fixture Material	Die-cast aluminum
Trim Finish	Powder coated white
Reflector	Polycarbonate with aluminum coating reflector
Glass/Diffuser	Frosted Polycarbonate
Driver	Internal
Binning	3 Step MacAdam
Lifespan	50,000 hours

LED Chip	CREE COB
dimensions (A*B*C*D)	6W - Ø98x29x135xØ65
Suspension	1.2m soft wire
Input Voltage	180~240VAC, 50/60Hz
Color Rendering Index	>85
Driver Protection	Short circuit
Operating Temperature	-20° to 50°C
Warranty	5 years against manufacturing defects
Agency Approval	CE, RoHS
Weight	420g



Available Power (W) & Dimension (A*B*C*D)	Available color Temperatures	LED Chip Lumen Efficacy			Power Factor	Available Beam Angles
		3000K	4000K	6000K		
• 6W: Ø98x29x135xØ65 • 12W: Ø98x29x150xØ90 • 20W: Ø98x29x197xØ107	2700K 3000K 4000K 6000K	80lm/W	85lm/W	90lm/W	> 0.9	36°

Standard option.

Non-standard products may be subject to MOQ. Contact your regional sales representative for more information.