

## **INSTALLATION INSTRUCTIONS**


TL110007


## Important Instructions. Please read first.

- Please follow instructions carefully. Failure to do so will void warranty. Please ensure installation complies with local law and applicable standards.
  - 1. Only use a GLP power supply unit.
  - 2. Ensure correct input voltage is connected to the luminaire.
  - 3. Ensure the power is disconnected before making any connections.
  - 4. Do not make modification or alter the luminaire without written approval of GLP.
  - 5. Ensure to keep luminaire in a clean area free of debris.


## **INSTALLATION**


- **Step 1:** Find the location where the luminaire has to be installed. Install a suitable wiring from the main supply (180-250VAC, 50/60Hz) to the luminaire.
- Step 2: Dig the mounting hole 20cm or deeper before installing the sleeve. Install the sleeve in the hard surface.





 Step 3: Depending on tile thickness, raise the recessed sleeve by 1-2cm above the surface. Connect the luminaire input cable to the main supply (180-250V AC, 50/60Hz) using a waterproof KIT.







Tel: +971 4 340 44 58





• Step 4: Ensure the waterproof KIT is installed within 30cm from the luminaire. Please make sure the earth (ground) wire is reliable. Solder and Wrap the connections with 3M waterproof tape & electrical tape. Fill the M11 kit with epoxy as illustrated.





• Step 5: Fix the luminaire to the sleeve by press.







Make sure the main power is switched off during installation.