




ZORA-MR660166

5W LED ENGINE



PRODUCT SPECIFICATIONS

| | |
|------------------|--|
| Fixture material | Die-cast Aluminum |
| Fixture finish | Powder coated gray |
| Driver | External |
| Dimmability | Non-dimmable. Also available in standard phase dimming or 0-10V or DALI dimming system |
| Binning | 3 Step MacAdam |
| Life Span | 50,000 hours |

| | |
|-----------------------|---------------------------------------|
| LED Chip | CREE |
| Power Consumption | 5W |
| Input Voltage | 180~240VAC, 50/60Hz |
| Operating Temperature | from -20° to 50° C |
| Color Rendering Index | ≥90 |
| Warranty | 2 years against manufacturing defects |
| Agency Approval | CE, RoHS |
| Weight | 200g |



| Power (W) | Available color Temperatures | LED Chip Lumen Efficacy | | | Power Factor | Available Beam Angles |
|-----------|----------------------------------|-------------------------|--------|--------|--------------|-----------------------|
| | | 3000K | 4000K | 6000K | | |
| 5W | 2700K 3000K 4000K 6000K | 80lm/W | 85lm/W | 90lm/W | 0.9 | 20° 40° |

Standard option.

Non-standard products may be subject to MOQ. Contact your regional sales representative for more information.