


SHAMA-PL110413

25W HANGING LIGHT





PRODUCT SPECIFICATIONS

| Fixture Material | Die-cast aluminum | | |
|------------------|---|--|--|
| Fixture Finish | Powder-coated black | | |
| Reflector | Polycarbonate with aluminum coating | | |
| Suspension | 1.5m rubber cable | | |
| Driver | Built-in | | |
| Dimmability | Non-Dimmable. Also available Standard Phase Dimming. | | |
| Binning | 3 Step MacAdam | | |
| Life Span | 40,000 hours | | |

| LED Chip | CREE COB | | |
|-----------------------|---------------------------------------|--|--|
| Power Consumption | 25W | | |
| Input Voltage | 180~250VAC 50/60Hz | | |
| Operating Temperature | from -20° to 50° C | | |
| Color Rendering Index | >80 | | |
| Warranty | 5 years against manufacturing defects | | |
| Agency Approval | CE, RoHS | | |





| Power (W) | Available color Temperatures | | | | Available | |
|--------------|----------------------------------|--------|--------|--------|--------------|-------------------|
| | | 3000K | 4000K | 6000K | Power Factor | Beam Angles |
| 25W | 2700K 3000K 4000K 6000K | 80lm/W | 85lm/W | 90lm/W | > 0.9 | 10° 36° 24° |

Standard option.

Non-standard products may be subject to MOQ. Contact your regional sales representative for more information.