

ZIYA - TL110012

3W COMPACT RECESSED UP LIGHT



PRODUCT SPECIFICATIONS

| | |
|-----------------------|--|
| Trim Material | Grade 316 stainless steel |
| Trim Finish | Polished stainless steel |
| Glass | Tempered frosted glass |
| Fixture Material | Grade 316 stainless steel |
| Sleeve Material | Black Polycarbonate |
| Static Load Pressure | 750kg |
| Driver | Built-in |
| LED Chip | Nichia |
| Binning | 3 step MacAdam |
| Wiring | 1 meter of 3 core 0.75mm ² rubber cable |
| Lifespan | 50,000 hours |
| Color Rendering Index | >85 |
| Input Voltage | 180-250VAC, 50/60 Hz |
| Driver Protection | Short circuit |
| Operating Temperature | from -20° to 65°C |
| Warranty | 3 years against manufacturing defects |



| Power (W) | Available Color Temperatures | Luminous Flux | | | IP Rating | Available Beam Angle |
|-----------|----------------------------------|---------------|---------|---------|-----------|----------------------|
| | | 3000K | 4000K | 6000K | | |
| 3W | 2700K 3000K 4000K 6000K | 110lm/W | 120lm/W | 130lm/W | 65 | 120° |

Standard option

Non-standard products may be subject to MOQ. Contact your regional sales representative for more information.